



WGM100PC120T1

1200V, 100A three-phase PIM IGBT Module with Trench Field Stop technology .The Power Integrated module with integration of rectifier and brake chopper.



Features:

- Trench-FS IGBT
- Low V_{CE} set
- Low Switching Loss
- Low L_s
- $T_j \text{ max}=175^\circ\text{C}$
- 100%RBSOA Tested (2lc)
- V_{CE} set with positive temp. coefficient
- RoHS



Applications:

- Motor Drives
- Servo Drives

Maximum Rated Valued of IGBT,Inverter

集电极-发射极电压 Collector-emitter voltage	V_{CES}	$T_j=25^\circ\text{C}$	1200	V
栅极-发射极峰值电压 Gate-emitter peak voltage	V_{GES}		± 20	V
连续集电极电流 Continuous collector current	I_c	$T_c=100^\circ\text{C}$ $T_c=25^\circ\text{C}$	100 200	A
集电极重复峰值电流 Repetitive peak collector current	I_{CM}	$T_j=175^\circ\text{C}, t_p=1\text{ms}$	200	A
最大损耗功率 Maximum power dissipation per IGBT	P_D	$T_c=25^\circ\text{C}$ $T_j \text{ max}=175^\circ\text{C}$	714	W



Electrical Characteristics of IGBT,Inverter

Min. Typ. Max.

集电极-发射极饱和电压 Collector-emitter saturation voltage	$V_{CE\text{ sat}}$	$I_C=100A, V_{GE}=15V$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		1.7 1.9 1.9	2.0	V V V
栅极阈值电压 Gate threshold voltage	$V_{GE(\text{th})}$	$I_C=1mA, V_{CE}=V_{GE},$	$T_J=25^\circ C$	5.0	5.5	6.6	V
栅极电荷 Gate charge	Q_G	$V_{GE} = -15 V \dots +15 V$	$T_J=25^\circ C$		0.75		uC
内部栅极电阻 Internal gate resistor	$R_{G\text{int}}$		$T_J=25^\circ C$		7.5		Ω
输入电容 Input capacitance	C_{ies}	$f=1MHz, V_{CE}=25V, V_{GE}=0V$	$T_J=25^\circ C$		8.03		nF
反向传输电容 Reverse transfer capacitance	C_{res}	$f=1MHz, V_{CE}=25V, V_{GE}=0V$	$T_J=25^\circ C$		1.22		nF
集电极-发射极截止电流 Collector-emitter cut-off current	I_{CES}	$V_{CE}=1200V, V_{GE}=0V$	$T_J=25^\circ C$		1		mA
栅极-发射极漏电流 Gate-emitter leakage current	I_{GES}	$V_{CE}=0V, V_{GE}=\pm 20V$	$T_J=25^\circ C$		200		nA
开通延迟时间 (电感负载) Turn-on delay time	$t_{d\text{ on}}$	$V_{CC}=600V, I_C=100A, R_{Gon}=1\Omega, V_{GE}=\pm 15V$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		228 250 254		ns ns ns
上升时间 (电感负载) Rise time	t_r	$V_{CC}=600V, I_C=100A, R_{Gon}=1\Omega, V_{GE}=\pm 15V$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		63 67 69		ns ns ns
关断延迟时间 (电感负载) Turn-off delay time	$t_{d\text{ off}}$	$V_{CC}=600V, I_C=100A, R_{Goff}=1\Omega, V_{GE}=\pm 15V$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		269 279 284		ns ns ns
下降时间 (电感负载) Fall time	t_f	$V_{CC}=600V, I_C=100A, R_{Goff}=1\Omega, V_{GE}=\pm 15V$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		184 291 317		ns ns ns
开通损耗能量 (电感负载) Turn-on energy loss per pulse	E_{on}	$V_{CC}=600V, I_C=100A, R_{Gon}=1\Omega, V_{GE}=\pm 15V$ $di/dt=1387A/us (T_J=150^\circ C)$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		3.1 4.3 4.8		mJ mJ mJ
关断损耗能量 (电感负载) Turn-off energy loss per pulse	E_{off}	$V_{CC}=600V, I_C=100A, R_{Goff}=1\Omega, V_{GE}=\pm 15V$ $du/dt=4448V/us (T_J=150^\circ C)$	$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$		5.28 8.33 9.3		mJ mJ mJ
短路数据 SC data	I_{sc}	$V_{GE}=\pm 15V, V_{CC}=600V, R_G=1\Omega, t_P=10us$	$T_J=25^\circ C$		575		A
结-外壳热阻 Thermal resistance, junction to case	$R_{th\text{ JC}}$	per leg			0.21		K/W



Maximum Rated Value of Diode,Inverter

反向重复峰值电压 Repetitive peak reverse voltage	V _{RRM}		T _C =25°C	1200	V
正向连续电流 continuous forward current	I _F		T _C =25°C	100	A
正向峰值电流 Maximum forward voltage	I _{FM}	t _P =1ms	T _C =25°C	200	A

Electrical Characteristics of Diode,Inverter

				Min.	Typ.	Max.
正向电压 Forward voltage	V _F	I _F =100A	T _J =25°C T _J =125°C T _J =150°C	1.70 1.80 1.80	V V V	
反向恢复峰值电流 Peak reverse recovery current	I _{RM}	V _R =600V, I _F =100A, V _{GE} =-15V -di/dt=1911A/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C	92 104 105	A A A	
反向恢复时间 Reverse recovery time	t _{rr}	V _R =600V, I _F =100A, V _{GE} =-15V -di/dt=1911A/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C	260 396 454	ns ns ns	
反向恢复电荷 Reverse Recovery charge	Q _r	V _R =600V, I _F =100A, V _{GE} =-15V -di/dt=1911A/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C	10.2 16.8 19.2	uC uC uC	
反向恢复损耗 (每脉冲) Reverse recovery energy	E _{rec}	V _R =600V, I _F =100A, V _{GE} =-15V -di/dt=1911A/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C	4.83 7.92 9.13	mJ mJ mJ	
结-外壳热阻 Thermal resistance, junction to case	R _{th JC}	per leg		0.34		K/W

Maximum Rated Value of IGBT,Brake-Chopper

集电极-发射极电压 Collector-emitter voltage	V _{CES}	T _J =25°C	1200	V
栅极-发射极峰值电压 Gate-emitter peak voltage	V _{GES}		±20	V
连续集电极电流 Continuous collector current	I _C	T _C =100°C T _C =25°C	50 100	A
集电极重复峰值电流 Repetitive peak collector current	I _{CM}	T _J =150°C, t _P =1ms	100	A
最大损耗功率 Maximum power dissipation per IGBT	P _D	T _C =25°C T _{J max} =175°C	398	W



Electrical Characteristics of IGBT, Brake-Chopper

					Min.	Typ.	Max.
集电极-发射极饱和电压 Collector-emitter saturation voltage	V _{CE sat}	I _C =50A, V _{GE} =15V	T _J =25°C T _J =125°C T _J =150°C		1.7 1.9 1.9	2.0	V V V
栅极阈值电压 Gate threshold voltage	V _{GE(th)}	I _C =1mA, V _{CE} =V _{GE} ,	T _J =25°C	5.0	5.5	6.6	V
栅极电荷 Gate charge	Q _G	V _{GE} = -15 V ... +15 V	T _J =25°C		0.51		uC
内部栅极电阻 Internal gate resistor	R _{Gint}		T _J =25°C		4		Ω
输入电容 Input capacitance	C _{ies}	f=1MHz, V _{CE} =25V, V _{GE} =0V	T _J =25°C		3.65		nF
反向传输电容 Reverse transfer capacitance	C _{res}	f=1MHz, V _{CE} =25V, V _{GE} =0V	T _J =25°C		0.5		nF
集电极-发射极截止电流 Collector-emitter cut-off current	I _{ces}	V _{CE} =1200V, V _{GE} =0V	T _J =25°C			1	mA
栅极-发射极漏电流 Gate-emitter leakage current	I _{ges}	V _{CE} =0V, V _{GE} =±20V	T _J =25°C			100	nA
开通延迟时间 (电感负载) Turn-on delay time	t _{d on}	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V	T _J =25°C T _J =125°C T _J =150°C		154 169 174		ns ns ns
上升时间 (电感负载) Rise time	t _r	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V	T _J =25°C T _J =125°C T _J =150°C		51 54 56		ns ns ns
关断延迟时间 (电感负载) Turn-off delay time	t _{d off}	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V	T _J =25°C T _J =125°C T _J =150°C		202 216 225		ns ns ns
下降时间 (电感负载) Fall time	t _f	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V	T _J =25°C T _J =125°C T _J =150°C		220 379 407		ns ns ns
开通损耗能量 (电感负载) Turn-on energy loss per pulse	E _{on}	V _{CC} =600V, I _C =50A, R _{Gon} =15Ω, V _{GE} =±15V di/dt=791A/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C		3.37 5.1 5.53		mJ mJ mJ
关断损耗能量 (电感负载) Turn-off energy loss per pulse	E _{off}	V _{CC} =600V, I _C =50A, R _{Goff} =15Ω, V _{GE} =±15V du/dt=3488V/us (T _J =150°C)	T _J =25°C T _J =125°C T _J =150°C		2.42 4.09 4.52		mJ mJ mJ
短路数据 SC data	I _{sc}	V _{GE} =±15V, V _{CC} =600V, R _C =15Ω, t _P =10us	T _J =25°C		297		A
结-外壳热阻 Thermal resistance, junction to case	R _{th JC}	per leg			0.38		K/W



Maximum Rated Value of Diode, Brake-Chopper

反向重复峰值电压 Repetitive peak reverse voltage	V_{RRM}		$T_c=25^\circ C$	1200	V
正向连续电流 continuous forward current	I_F		$T_c=25^\circ C$	35	A
正向峰值电流 Maximum forward voltage	I_{FM}	$t_P=1ms$	$T_c=25^\circ C$	70	A

Electrical Characteristics of Diode, Brake-Chopper

				Min.	Typ.	Max.
正向电压 Forward voltage	V_F	$I_F=35A$		$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$	2.0 2.1 2.1	2.2 V V
反向恢复峰值电流 Peak reverse recovery current	I_{RM}	$V_R=600V, I_F=35A, V_{GE}=-15V$ $-di/dt=590A/us (T_J=150^\circ C)$		$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$	15.1 19.2 20.6	A A A
反向恢复时间 Reverse recovery time	t_{rr}	$V_R=600V, I_F=35A, V_{GE}=-15V$ $-di/dt=590A/us (T_J=150^\circ C)$		$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$	320 450 480	ns ns ns
反向恢复电荷 Reverse Recovery charge	Q_r	$V_R=600V, I_F=35A, V_{GE}=-15V$ $-di/dt=590A/us (T_J=150^\circ C)$		$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$	1.8 3.5 4.2	uC uC uC
反向恢复损耗 (每脉冲) Reverse recovery energy	E_{rec}	$V_R=600V, I_F=35A, V_{GE}=-15V$ $-di/dt=590A/us (T_J=150^\circ C)$		$T_J=25^\circ C$ $T_J=125^\circ C$ $T_J=150^\circ C$	0.5 1.2 1.6	mJ mJ mJ
结-外壳热阻 Thermal resistance, junction to case	$R_{th JC}$	per leg			0.65	K/W

Maximum Rated Value of Diode, Rectifier

反向重复峰值电压 Repetitive peak reverse voltage	V_{RRM}		$T_J=25^\circ C$	1800	V
最大正向均方根电流 Maximum RMS forward current	I_{FRMSM}	per chip	$T_J=80^\circ C$	130	A
最大整流器输出均方根电流 Maximum RMS current at rectifier output	I_{RMSM}		$T_J=80^\circ C$	180	A
正向浪涌电流 Surge forward current	I_{FSM}	$t_P=10ms$	$T_J=25^\circ C$ $T_J=150^\circ C$	1500 1150	A
I^2t I^2t -Value	I^2t	$t_P=10ms$	$T_J=25^\circ C$ $T_J=150^\circ C$	11560 6610	A^2s



Electrical Characteristics of Diode, Rectifier

					Min.	Typ.	Max.
正向电压 Forward voltage	V _F	I _F =85A	T _J =25°C T _J =125°C T _J =150°C		1.0 0.9 0.9		V V V
反向恢复峰值电流 Reverse current	I _R	V _R =1800V	T _J =25°C			1	mA
结-外壳热阻 Thermal resistance, junction to case	R _{th JC}	per leg		0.29			K/W

NTC-Thermistor

额定电阻值 Rated resistance	R ₂₅	T _c =25°C	5		KΩ
R100 偏差 Deviation of R100	△R/R	T _c =100°C, R ₁₀₀ =481Ω		±5	%
耗散功率 Power dissipation	P ₂₅	T _c =25°C	50		mW
B-值 B-Value	B _{25/50}	R ₂ =R ₂₅ exp[B _{25/50} (1/T ₂ -1/(298.15K))]	3380		K
B-值 B-Value	B _{25/80}	R ₂ =R ₂₅ exp[B _{25/80} (1/T ₂ -1/(298.15K))]	3440		K

Module

			Min.	Typ.	Max.
绝缘电压 Isolation voltage	V _{iso}	f=50Hz, t=1min, RMS, All terminals shorted	2500		V
模块寄生电感 Stray Inductance Module	L _s			40	nH
相对电痕指数 Comparative tracking index	CTI		200		V
最高结温 Maximum junction temperature	T _{J max}		-40	175	°C
工作结温 Operating junction temperature	T _{J OP}		-40	150	°C
储存温度 Storage temperature	T _{stg}		-40	125	°C
外壳-散热器热阻 Thermal resistance, case to heatsink	R _{thCH}	Thermal grease applied		0.10	K/W
安装扭矩 Mounting torque	T	Mounting screw: M5	3.0	5.0	N·m N·m
重量 Weight	G			300	g



Fig.1 Typical saturation voltage characteristics vs temp.
IGBT, Inverter




Fig.3 Transfer Characteristic VS V_{GE}
IGBT, Inverter




Fig.2 Typical output characteristics vs V_{GE}
IGBT, Inverter




Fig.4 Typical switching loss vs Collector current
IGBT, Inverter




Fig.5 Typical switching loss vs Gate resistance
IGBT, Inverter




Fig.7 Capacitance Characteristics
IGBT, Inverter




Fig.6 Transient thermal impedance
IGBT, Inverter




Fig.8 Typical forward characteristic
Diode, Inverter




Fig.9 Typical switching loss vs Forward current
Diode, Inverter




Fig.11 Transient thermal impedance
Diode, Inverter




Fig.10 Typical switching loss vs R_G
Diode, Inverter




Fig.12 Typical saturation voltage characteristics vs temp.
IGB, Brake-Chopper




Fig.13 Typical forward characteristic

Diode, Brake-Chopper




Fig.15 Reverse bias safe operating area (RBSOA)




Fig.14 Typical forward characteristic

Diode, Rectifier







Fig.16 NTC Temperature Characteristics



Internal circuit (接线图)**Package outline (mm) (封装尺寸)**

Contact Information

No.1001, Shiwan(7) Road, Pudong District, Shanghai, P.R.China.201202

Tel: 86-21-50310888 Fax: 86-21-50757680 Email: WAYON website:

<http://www.way-on.com>

For additional information, please contact your local Sales Representative.

 ® is registered trademarks of Wayon Corporation.

Disclaimer

WAYON reserves the right to make changes without further notice to any Products herein to improve reliability, function, or design. The Products are not designed for use in hostile environments, including, without limitation, aircraft, nuclear power generation, medical appliances, and devices or systems in which malfunction of any Product can reasonably be expected to result in a personal injury. The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. WAYON does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Products or technical information described in this document.

